



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: CLEAR POLYMER CHAIN LUBRICANT

Article number: R228

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product category: PC24: Lubricants, greases, release products

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: TYGRIS Industrial

Unit 31, Kyle Road Industrial Estate

Irvine Ayrshire KA12 8LE

Tel +44 (0) 1294 311 066 Fax +44 (0) 1294 277 115

Email technical@tygrisindustrial.com

Further information obtainable from:

Technical Department

1.4 Emergency telephone

number:

Tel +44 (0) 1294 311 066





SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Physical hazards: Flam. Aerosol 1 - H222

Health hazards: Skin Irrit. 2 - H315, STOT SE 3 - H336

Environment hazards: Aquatic Chronic 2 - H411

2.2. Label elements

Hazard statements: H222: Extremely flammable aerosol.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark GHS09: Environmental







Signal word: Danger

Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211: Do not spray on an open flame or other ignition source. P251: Pressurized container: Do not pierce or burn, even after use.

P261: Avoid breathing vapour/spray.

P271: Use only outdoors or in a well-ventilated area.

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501: Dispose of contents/container in accordance with local regulations.

Supplementary P264: Wash contaminated skin thoroughly after handling. P321: Specific treatment (see medical advice on this label).

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell. P332+313: If skin irritation occurs: Get medical advice/attention. P362: Take off contaminated clothing and wash before reuse.

P403+233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

Additional information: H229: Pressurised container: May burst if heated

2.3. Other hazards





SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

NAPHTHA (PETROLEUM) , HYDROTREATED LIGHT Registration Number: 01-2119475514-35-xxxx

| EC | CAS | Index number | CLP Classification | Percent |
|----------------|------------|--------------|--|---------|
| 921-024-6 | 64742-49-0 | - | Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411 | 10-30% |
| BUTANE | | | | |
| 203-448-7 | 106-97-8 | - | Flam. Gas 1 - H220 | 10-30% |
| ISOBUTANE | | | | |
| 200-857-2 | 75-28-5 | - | Flam. Gas 1 - H220 | 5-10% |
| MINERAL OIL (F | REFINED) | | | |
| 265-155-0 | 64742-52-5 | - | Not classified. | 1-5% |
| XYLENE | | | | |
| 215-535-7 | 1330-20-7 | - | Flam. Liq. 3 - H226 Acute Tox. 4 - H312, H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412 | < 1% |
| PROPAN-2-OL | | | l | I |
| 200-661-7 | 67-63-0 | - | Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336 | < 1% |
| | | | I . | |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.







SECTION 4: First aid measures

4.1. Description of first aid measures

General information: Move the exposed person to fresh air at once. Get medical attention if any discomfort

Skin contact: Wash the skin immediately with soap and water. Get medical attention if any discomfort

continues.

Eye contact: Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes

with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get

medical attention if any discomfort continues.

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts Ingestion:

of milk or water to people not unconscious. Get medical attention if any discomfort

continues.

Move the exposed person to fresh air at once. When breathing is difficult, properly trained Inhalation:

personnel may assist affected person by administering oxygen. Keep the affected person

warm and at rest. Get prompt medical attention.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

Extinguishing media

Extinguishing media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Aerosol cans may explode in a fire.

5.3. Advice for fire-fighters

Special fire fighting procedures:

Containers close to fire should be removed or cooled with water. Use water to keep

fire exposed containers cool and disperse vapours.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks,

flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces

because of explosion risk. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections



SECTION 7: Handling and storage

7.1 Precautions for safe handling

Handling requirements: Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate

well, avoid breathing vapours. Use approved respirator if air contamination is above

accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

BUTANE

| Long-term exposure limit (8-hour TWA) | Short-term exposure limit (15-minute) |
|---------------------------------------|---------------------------------------|
| WEL 600 ppm, 1450 mg/m ³ | WEL 750 ppm, 1810 mg/m³ |

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT

MINERAL OIL (REFINED)

PROPAN-2-OL

| WEL 400 ppm, 999 mg/m ³ | WEL 500 ppm, 1250 mg/m ³ |
|------------------------------------|-------------------------------------|
|------------------------------------|-------------------------------------|

XYLENE

| WEL 50 ppm, 220 mg/m ³ | WEL 100 ppm, 441 mg/m ³ |
|-----------------------------------|------------------------------------|

WEL = Workplace Exposure Limits



SAFETY DATA SHEET



CLEAR POLYMER CHAIN LUBRICANT R228

8.2. Exposure controls

Protective equipment:





Engineering measures: Provide adequate general and local exhaust ventilation.

General protective and hygienic measures:

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes

contaminated. When using do not eat, drink or smoke.

Respiratory protection: No specific recommendation made, but respiratory protection must be used if the general

level exceeds the recommended occupational exposure limit. Use chemical cartridge

protection with appropriate cartridge.

Use protective gloves. Hand protection:

Use approved safety goggles or face shield. Eye protection:

Other Protection: Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapour contact.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol Colour: Yellow

Odour: Characteristic Solubility: Insoluble in water

Flammability limits: Lower: 0.8 % Upper: 9.0 %

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable under normal temperature conditions. Chemical stability:

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents.

Strong alkalis. Strong mineral acids.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).



Version 2





SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin contact: Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent

on skin. May cause cracking of skin, and eczema.

Eye contact: Irritating to eyes. May cause chemical eye burns.

Inhalation: May cause irritation to the respiratory system. Vapours may cause headache, fatigue,

dizziness and nausea. Prolonged inhalation of high concentrations may damage

respiratory system. Irritating to respiratory system.

Ingestion: May cause discomfort if swallowed. May cause stomach pain or vomiting.

Gastrointestinal symptoms, including upset stomach.

Route of entry: Inhalation. Skin and/or eye contact.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity: Dangerous for the environment if discharged into watercourses.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information: Empty containers must not be burned because of explosion hazard. Dispose of waste

and residues in accordance with local authority requirements.





SECTION 14: Transport information

UN Number (ADR): 1950
UN Number (IMDG): 1950
UN Number (IATA): 1950

14.2 UN proper shipping name

Proper shipping name:

AEROSOLS

14.3. Transport hazard class(es)

ADR/RID/ADN Class: 2, Class 2: Gases

ADR Label No. 2.1
IMDG Class: 2.1
ICAO Class/Division: 2.1

Transport labels:



14.4. Packing group

Packing group: Not applicable.

14.5 Environmental hazards

Marine pollutant: No 14.6 Special precautions for user

EmS: F-D, S-U

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments: The Aerosol Dispensers (Amendment) Regulations 2014 No.1130.

Guidance Notes: Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

EU Legislation: The Aerosol Dispensers Directive 1975/324 EEC.

Regulation (EC) No.1272/2008: The Classification, Labelling and Packaging of

substances and mixtures Regulations.

Regulation (EC) No. 1907/2006: The Registration, Evaluation, Authorisation and

Restriction of Chemicals Regulations (REACH).

2001/95/EC The General Product Safety Directive (GPSD).

Commission Regulation (EU) 2015/830: Requirements for the compilation of safety data

sheets (amending REACH).

Authorisations (Title VII Regulation 1907/2006): No specific authorisations are noted for

this product.

Restrictions (Title VIII Regulation 1907/2006): No specific restrictions of use are noted

for this product.

15.2. Safety, health and environmental regulations/legislation specific for the substance or mixture







SECTION 16: Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H222: Extremely flammable aerosol. H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation. H336: May cause drowsiness or dizziness.

H373: May cause damage to organs << Organs>> through prolonged or repeated exposure.

H411: Toxic to aquatic life with long lasting effects. H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer The above information is believed to be correct but does not purport to be all inclusive and

shall be used only as a guide. This company shall not be held liable for any damage

resulting from handling or from contact with the above product.

