SAFETY DATA SHEET



HEAVY DUTY ZINC GALVE SPRAY R239

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

HEAVY DUTY ZINC GALVE SPRAY

Article number:

Trade name:

R239

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:	TYGRIS Industrial Unit 31, Kyle Road Industrial Estate Irvine Ayrshire KA12 8LE Tel +44 (0) 1294 311 066 Fax +44 (0) 1294 277 115 Email technical@tygrisindustrial.com
Further information obtainable from:	Technical Department

1.4 Emergency telephone number:

Tel +44 (0) 1294 311 066



SAFETY DATA SHEET

TYGRIS

HEAVY DUTY ZINC GALVE SPRAY R239

SECTION 2: Hazards identification

OLOTION 2. Hazards identificat	
2.1. Classification of the substa	nce or mixture
Physical hazards:	Flam. Aerosol 1 - H222
Health hazards:	EUH066, Acute Tox. 4 - H312, Acute Tox. 4 - H332, Eye Irrit. 2 - H319
Environment hazards:	Aquatic Chronic 2 - H411
2.2. Label elements	
Hazard statements:	H222: Extremely flammable aerosol. H312: Harmful in contact with skin. H319: Causes serious eye irritation. H332: Harmful if inhaled. H411: Toxic to aquatic life with long lasting effects.
Hazard pictograms:	GHS02: Flame GHS07: Exclamation mark GHS09: Environmental
Signal word:	Danger
Precautionary statements:	 P102: Keep out of reach of children. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211: Do not spray on an open flame or other ignition source. P251: Pressurized container: Do not pierce or burn, even after use. P261: Avoid breathing vapour/spray. P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves/protective clothing/eye protection/face protection. P305+351 +338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+313: If eye irritation persists: Get medical advice/attention. P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501: Dispose of contents/container in accordance with local regulations.
Supplementary precautionary statements:	 P264: Wash contaminated skin thoroughly after handling. P302+352: IF ON SKIN: Wash with plenty of soap and water. P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P312: Call a POISON CENTER or doctor/physician if you feel unwell. P322: Specific measures (see on this label). P363: Wash contaminated clothing before reuse.
Additional information:	EUH066: Repeated exposure may cause skin dryness or cracking. Contains: SOL007 Xylene (mixture of isomers) H229: Pressurised container: May burst if heated
2.3. Other hazards	



31 Kyle Road, Irvine KA12 8LE Tel: +44 (0) 1294 311 066 technical@tygrisindustrial.com Compilation Date: 21/10/2021 Version 2 Page 2 of 8

TGRIS

HEAVY DUTY ZINC GALVE SPRAY R239

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ACETONE

EC	CAS	Index number	CLP Classification	Percent
200-662-2	67-64-1	-	Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336 EUH066	10-30%

BUTANE

203-448-7 106-97-8 - Flam. Gas 1 - H220 10-30%		10-3070
--	--	---------

XYLENE

215-535-7	1330-20-7	-	Flam. Liq. 3 - H226 Acute Tox. 4 - H312, H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic	10-30%
			Chronic 3 - H412	

ZINC DUST

	tic Acute 1 - H400 10-30% tic Chronic 1 - H410
--	--

ISOBUTANE

200-857-2	75-28-5	-	Flam. Gas 1 - H220	5-10%
-----------	---------	---	--------------------	-------

1-METHOXY-2-PROPANOL

203-539-1 107-98-2 -	Flam. Liq. 3 - H226 STOT SE 3 - H336	1-5%
----------------------	---	------

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.



T GRIS

HEAVY DUTY ZINC GALVE SPRAY R239

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:	Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.
Skin contact:	Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.
Eye contact:	Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.
Ingestion:	DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.
Inhalation:	Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measu	Jres
5.1 Extinguishing media	
Extinguishing media:	Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.
5.2. Special hazards arising fro	om the substance or mixture
Exposure hazards:	Aerosol cans may explode in a fire.
5.3. Advice for fire-fighters	
Special fire fighting procedures:	Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.
SECTION 6: Accidental release	e measures

6.1. Personal precautions, protective equipment and emergency procedures

- 6.2. Environmental precautions
- 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections



TYGRIS

SAFETY DATA SHEET

HEAVY DUTY ZINC GALVE SPRAY R239

SECTION 7: Handling and storage

	iugo		
7.1 Precautions for safe handling			
Handling requirements:		Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.	
7.2. Conditions for safe stora	ge, including any incompati	ibilities	
Storage conditions:	Aerosol cans: Must not be	Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.	
7.3. Specific end use(s)			
SECTION 8: Exposure control	ls/personal protection		
8.1. Control parameters			
Workplace exposure limits:			
ACETONE			
Long-term exposure limit (8-ho	our TWA)	Short-term exposure limit (15-minute)	
WEL 500 ppm, 1210 mg/m ³		WEL 1500 ppm, 3620 mg/m ³	
BUTANE			
WEL 600 ppm, 1450 mg/m ³		WEL 750 ppm, 1810 mg/m ³	
XYLENE			
WEL 50 ppm, 220 mg/m ³		WEL 100 ppm, 441 mg/m ³	
1-METHOXY-2-PROPANOL			
WEL 100 ppm (Sk), 375 mg/m	13	WEL 150 ppm (Sk), 560 mg/m ³	
WFL = Workplace Exposure Li	mits		

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment:



Engineering measures: Provide adequate general and local exhaust ventilation. General protective and DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before hygienic measures: eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke. No specific recommendation made, but respiratory protection must be used if the general **Respiratory protection:** level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge. Use protective gloves. Hand protection: Use eye protection. Eye protection: Wear appropriate clothing to prevent any possibility of liquid contact and repeated or Other Protection: prolonged vapour contact.



TYGRIS

HEAVY DUTY ZINC GALVE SPRAY R239

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties		
State:	Aerosol	
Colour:	Grey	
Odour:	Characteristic	
Solubility:	Insoluble in water	
Flammability limits:	Lower: 0.8 % Upper: 9.0 %	
9.2. Other information		

Volatile organic compound 608 g/litre (VOC):

SECTION 10: Stability and reactivity

10.1. Reactivity		
10.2. Chemical stability		
Chemical stability:	Stable under normal temperature conditions.	
10.3. Possibility of hazardous reactions		
10.4. Conditions to avoid		
Conditions to avoid:	Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.	
10.5. Incompatible materials		
10.6. Hazardous decomposition products		
Fire creates:	Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).	
SECTION 11: Toxicological information		

11.1. Information on toxicological effects

Skin contact:	Harmful in contact with skin. Irritating to skin. Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.
Eye contact:	Irritating to eyes. May cause chemical eye burns.
Inhalation:	May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. Irritating to respiratory system.
Ingestion:	May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.
Route of entry:	Inhalation. Skin and/or eye contact.



T GRIS

SAFETY DATA SHEET

HEAVY DUTY ZINC GALVE SPRAY R239

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity:

Dangerous for the environment if discharged into watercourses.

- 12.2. Persistence and degradability
- 12.3. Bioaccumulative potential
- 12.4. Mobility in soil
- 12.5. Results of PBT and vPvB assessment
- 12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information:

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: Transport information

UN Number (ADR):	1950
UN Number (IMDG):	1950
UN Number (IATA):	1950
14.2 UN proper shipping name	
Proper shipping name:	AEROSOLS
14.3. Transport hazard class(es)	
ADR/RID/ADN Class:	2, Class 2: Gases
ADR Label No. IMDG	2.1
Class:	2.1
ICAO Class/Division:	2.1
Transport labels:	
14.4. Packing group	
Packing group:	Not applicable.
14.5 Environmental hazards	
Marine pollutant:	No
14.6 Special precautions for use	er
EmS:	F-D, S-U
14.7. Transport in bulk accordin	g to Annex II of MARPOL and the IBC Code



TYGRIS

SAFETY DATA SHEET

HEAVY DUTY ZINC GALVE SPRAY R239

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture		
Statutory Instruments:	The Aerosol Dispensers (Amendment) Regulations 2014 No.1130.	
Guidance Notes:	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37.	
EU Legislation:	 The Aerosol Dispensers Directive 1975/324 EEC. Regulation (EC) No.1272/2008: The Classification, Labelling and Packaging of substances and mixtures Regulations. Regulation (EC) No. 1907/2006: The Registration, Evaluation, Authorisation and Restriction of Chemicals Regulations (REACH). 2001/95/EC The General Product Safety Directive (GPSD). Commission Regulation (EU) 2015/830: Requirements for the compilation of safety data sheets (amending REACH). Authorisations (Title VII Regulation 1907/2006): No specific authorisations are noted for this product. Restrictions (Title VIII Regulation 1907/2006): No specific restrictions of use are noted for this product. 	

SECTION 16: Other information		
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.	
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking. H220: Extremely flammable gas. H222: Extremely flammable aerosol. H225: Highly flammable liquid and vapour. H226: Flammable liquid and vapour. H304: May be fatal if swallowed and enters airways. H312: Harmful in contact with skin. H315: Causes skin irritation. H319: Causes serious eye irritation. H319: Causes serious eye irritation. H332: Harmful if inhaled. H335: May cause respiratory irritation. H336: May cause drowsiness or dizziness. H373: May cause damage to organs < <organs>> through prolonged or repeated exposure. H400: Very toxic to aquatic life. H410: Very toxic to aquatic life with long lasting effects. H411: Toxic to aquatic life with long lasting effects. H412: Harmful to aquatic life with long lasting effects.</organs>	
Legal disclaimer	The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.	

