

# ANTI-STATIC FOAM CLEANER

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: ANTI-STATIC FOAM CLEANER

Article number: R245

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: TYGRIS Industrial

Unit 31, Kyle Road Industrial Estate

Irvine Ayrshire KA12 8LE

Tel +44 (0) 1294 311 066 Fax +44 (0) 1294 277 115

Email technical@tygrisindustrial.com

Further information obtainable from:

**Technical Department** 

1.4 Emergency telephone

number:

Tel +44 (0) 1294 311 066

#### **SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture

Physical hazards: Aerosol 1 - H222

2.2. Label elements

**Hazard statements:** H222: Extremely flammable aerosol.

Hazard pictograms: GHS02: Flame



Signal word: Danger

**Precautionary statements:** P102: Keep out of reach of children.

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P211: Do

not spray on an open flame or other ignition source.

P251: Pressurized container: Do not pierce or burn, even after use.

P261: Avoid breathing vapour/spray. P280: Wear protective gloves.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+313: If eye irritation persists: Get medical advice/attention.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50°

C/122°F.

P501: Dispose of contents/container in accordance with local regulations.

Supplemental label

information:

H229: Pressurised container: May burst if heated

Contains:

NATRIUMNITRIET, d-LIMONENE, SODIUM BENZOATE

2.3. Other hazards



# ANTI-STATIC FOAM CLEANER

### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### **Hazardous ingredients:**

#### PROPAN-2-OL

EC	CAS	Index number	CLP Classification	Percent
200-661-7	67-63-0	-	Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	10-30%
BUTANE				
203-448-7	106-97-8	-	Flam. Gas 1 - H220	5-10%
ISOBUTANE				
200-857-2	75-28-5	-	Flam. Gas 1 - H220	1-5%
SODIUM NITRIT	ГЕ	·		
231-555-9	7632-00-0	-	Ox. Sol. 3 - H272 Acute Tox. 3 - H301 Aquatic Acute 1 - H400	< 1%

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

General information: Move the exposed person to fresh air at once. Get medical attention if any discomfort

continues.

Wash the skin immediately with soap and water. Get medical attention if any discomfort Skin contact:

continues.

Eye contact: Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes

with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get

medical attention if any discomfort continues.

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts Ingestion:

of milk or water to people not unconscious. Get medical attention if any discomfort

continues.

Move the exposed person to fresh air at once. When breathing is difficult, properly trained Inhalation:

personnel may assist affected person by administering oxygen. Keep the affected person

warm and at rest. Get prompt medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

General information: NOTE! Effects may be delayed. Keep affected person under observation.

4.3. Indication of any immediate medical attention and special treatment needed







# ANTI-STATIC FOAM CLEANER R245

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media

**Extinguishing media:** Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Aerosol cans may explode in a fire.

5.3. Advice for fire-fighters

Special fire fighting

procedures:

Containers close to fire should be removed or cooled with water. Use water to keep

fire exposed containers cool and disperse vapours.

#### **SECTION 6: Accidental release measures**

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks,

flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces

because of explosion risk. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

#### **SECTION 7: Handling and storage**

7.1 Precautions for safe handling

**Handling requirements:** Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact.

Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is

above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)





# ANTI-STATIC FOAM CLEANER R245

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### Workplace exposure limits:

**BUTANE** 

Long-term exposure limit (8-hour TWA)	Short-term exposure limit (15-minute)
WEL 600 ppm, 1450 mg/m <sup>3</sup>	WEL 750 ppm, 1810 mg/m³

#### PROPAN-2-OL

WEL 400 ppm, 999 mg/m³	WEL 500 ppm, 1250 mg/m <sup>3</sup>
------------------------	-------------------------------------

### WEL = Workplace Exposure Limits

#### 8.2. Exposure controls

Protective equipment:





**Engineering measures:** Provide adequate general and local exhaust ventilation.

General protective and hygienic measures:

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes

contaminated. When using do not eat, drink or smoke.

Respiratory protection: No specific recommendation made, but respiratory protection must be used if the general

level exceeds the recommended occupational exposure limit. Use chemical cartridge

protection with appropriate cartridge.

Hand protection: Use protective gloves.

**Eye protection:** Wear approved chemical safety goggles where eye exposure is reasonably probable.

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

Other Protection: prolonged vapour contact.

### **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

State: Aerosol
Colour: White

Odour: Characteristic
Solubility: Flammability Soluble in water

limits: 9.2. Other Lower: 0.8 % Upper: 9.0 %

information

## **SAFETY DATA SHEET**



# ANTI-STATIC FOAM CLEANER R245

#### **SECTION 10: Stability and reactivity**

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Avoid heat, flames and other sources of ignition. Avoid contact with: Strong

oxidising agents. Strong alkalis. Strong mineral acids.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

#### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Skin contact: Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent

on skin. May cause cracking of skin, and eczema.

Eye contact: Irritating to eyes. May cause chemical eye burns.

**Inhalation:** May cause irritation to the respiratory system. Vapours may cause headache, fatigue,

dizziness and nausea. Prolonged inhalation of high concentrations may damage

respiratory system.

Ingestion: May cause discomfort if swallowed. May cause stomach pain or vomiting.

Gastrointestinal symptoms, including upset stomach.

Route of entry: Inhalation. Skin and/or eye contact.

### **SECTION 12: Ecological information**

12.1. Toxicity

**Ecotoxicity:** Dangerous for the environment if discharged into watercourses.

12.2. Persistence and degradability

Degradability: The surfactant(s) contained in this preparation complies(comply) with the biodegradability

criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will

be made available to them, at their direct request or at the request of a detergent

manufacturer.

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects







# ANTI-STATIC FOAM CLEANER R245

### **SECTION 13: Disposal considerations**

13.1. Waste treatment methods

General information: Empty containers must not be burned because of explosion hazard. Dispose of waste and

residues in accordance with local authority requirements.

## **SECTION 14: Transport information**

UN Number (ADR): 1950
UN Number (IMDG): 1950
UN Number (IATA): 1950

14.2 UN proper shipping name

Proper shipping name:

**AEROSOLS** 

14.3. Transport hazard class(es)

ADR/RID/ADN Class: 2, Class 2: Gases

ADR Label No. IMDG 2.1
Class: 2.1
ICAO Class/Division: 2.1

Transport labels:



14.4. Packing group

Packing group: Not applicable.

14.5 Environmental hazards

Marine pollutant: No

14.6 Special precautions for user

EmS: F-D, S-U

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code





## ANTI-STATIC FOAM CLEANER

### **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Statutory Instruments:** The Aerosol Dispensers (Amendment) Regulations 2014 No.1130.

**Guidance Notes:** Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

**EU Legislation:** The Aerosol Dispensers Directive 1975/324 EEC.

Regulation (EC) No.1272/2008: The Classification, Labelling and Packaging of

substances and mixtures Regulations.

Regulation (EC) No. 1907/2006: The Registration, Evaluation, Authorisation and

Restriction of Chemicals Regulations (REACH).

2001/95/EC The General Product Safety Directive (GPSD).

Commission Regulation (EU) 2015/830: Requirements for the compilation of safety data

sheets (amending REACH).

Authorisations (Title VII Regulation 1907/2006): No specific authorisations are noted for

this product.

Restrictions (Title VIII Regulation 1907/2006): No specific restrictions of use are noted

for this product.

#### 15.2. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **SECTION 16: Other information**

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H222: Extremely flammable aerosol. H225: Highly flammable liquid and vapour.

H272: May intensify fire; oxidiser. H301: Toxic if swallowed.

H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness.

H400: Very toxic to aquatic life.

The above information is believed to be correct but does not purport to be all inclusive and Legal disclaimer

shall be used only as a guide. This company shall not be held liable for any damage

resulting from handling or from contact with the above product.

